

What is claimed is:

1. A fluorescent display device comprising:

an envelop of which an inner space is in a vacuum  
5 state, the envelop having therein a plurality of filament-  
shaped cathodes supported by a pair of cathode supports; and  
anodes, each having a fluorescent material, fluorescent  
materials of the anodes radiating light by impaction of  
electrons emitted from the cathodes;

10 wherein each of the cathode supports includes a base  
fixed to the envelop; one or more anchors, each having an  
arm serving as a resilient member and a tab for supporting  
one end of a cathode, the arm having a distal end portion  
and a proximal end portion, the proximal end portion being  
15 connected to the base and the tab being disposed at the  
distal end portion; and one or more support members, each  
being connected to the base and separated from the arm of  
its adjacent anchor and supporting one end of another  
cathode.

20

2. The fluorescent display device of claim 1, wherein  
each of the cathode supports is formed by bending a shaped  
sheet, and the shaped sheet has a slit formed between each  
support member and its adjacent anchor, each support member  
25 and its adjacent anchor being seamlessly connected to the  
base.

3. A cathode support for use in a fluorescent display device including an envelop of which an inner space is in a vacuum state, the envelop having therein filament-shaped cathodes; and anodes, each anode having a fluorescent material, fluorescent materials of the anodes radiating light by impaction of electrons emitted from the cathodes, the cathode support supporting the cathodes inside the envelop and comprising:

10 a base fixed to the envelop;

one or more anchors, each having an arm serving as a resilient member and a tab for supporting one end of a cathode, the arm having a distal end portion and a proximal end portion, the proximal end portion being connected to the base and the tab being disposed at the distal end portion;

15 and

one or more support members, each being connected to the base and separated from the arm of its adjacent anchor and supporting one end of another cathode.

20